

## Features and advantages

- Safest LiFePO4 rechargeable battery
- Higher usable energy ratio, less self consumption
- 1/3 weight of equivalant capacity Lead-Acid battery
- Plug and Play, quick installation, up to 3 unit parallel
- Wide temperature range of -20~50°C
- Contains no toxic heavy metals or caustic materials





## **SPECIFICATION**

| Model                           | PowerDepot   |     |
|---------------------------------|--|-----|
| Battery Type                    | LiFePO4  |     |
| Battery Module                  | H2.5   | H5  |
| Battery Capacity [Ah]           | 50   | 100 |
| Nominal Battery Energy [kWh]    | 2.4  | 4.8 |
| Max Output Power [kW]           | 2.4  | 4.8 |
| Net Weight [Kg]                 | 44   | 65  |
| Dimension [H*W*D, mm]           | 574*228*600  |     |
| Working Voltage [V]             | 40.5~54  |     |
| Operating Temp. Range [°C]      | -20~50   |     |
| Calendar Life [Cycles] [1]      | 6000   |     |
| Nominal Voltage [V]             | 48   |     |
| Protection Level                | IP65   |     |
| Communication                   | CAN / RS485 / DRY CONTACT  |     |
| Certification & Safety Standard | CE / UN38.3  |     |
| Scalabilitty [kWh]              | Up to 3 units to parallel  |     |
| Compatible Inverters            | Goodwe Victron Imeon Solis Luxpower Growatt GMDE Sofar Voltronic Deye<br>More brands will be announced |     |
| Warranty                        | 10 Years   |     |
| Warranty Document Supplied      | Yes  |     |
| Color                           | White  |     |
| Alarms                          | Overcharge Overdischarge Overcurrent Overtemperature Short Circuit                                     |     |
| Pros                            | Can be used in both off-grid and hybrid setups, compact design, modular expansion                      |     |
| Monitoring & Protection         | Each module has BMS, breaker embedded in system  |     |

[1] Test conditions: 0.2C Charging/Discharging, @25°C, 80% Dod









